



## MAINTENANCE TIPS

# HSI Blow Bar Rotation Schedule: Double Your Wear Life with Proper Indexing

Learn the optimal HSI blow bar rotation schedule. Maximize wear life and maintain consistent product quality with proven 4-position indexing strategies.

**Author:** Sivabalan  
Selvarajan

**Published:** January 22,  
2026

**Reading  
Time:** 3  
minutes

HSI blow bar rotation strategy can double wear life while maintaining consistent product quality. Yet many operations run bars to complete failure, wasting 40-50% of potential wear life and risking rotor damage. This guide establishes systematic rotation protocols that extract maximum value from every blow bar while protecting critical crusher components.

## Blow Bar Wear Patterns

---

### Normal Wear Profile

A properly operating HSI develops characteristic wear on blow bars:

- **Leading Edge:** Highest wear (65-70% of total)
- **Trailing Edge:** Moderate wear (20-25%)
- **Body Surface:** Light polishing (10-15%)

## Wear Rate by Material

MATERIAL TYPE	TYPICAL WEAR (MM/1000T)	EXPECTED LIFE (TONNES)
Limestone (soft)	1.5-2.5	80,000-120,000
Granite (medium)	3-5	40,000-65,000
Basalt (hard)	5-8	25,000-40,000
Quartzite (abrasive)	8-12	15,000-25,000

## Rotation Protocol

### 4-Position Rotation Schedule

STAGE	BAR ORIENTATION	LIFE USED	REMAINING VALUE
1. Initial Install	New bar, edge 1 leading	0-35%	100%
2. First Rotation	Flip 180°, edge 2 leading	35-65%	65%
3. End-to-End Swap	Swap ends, edge 1 leading	65-85%	35%
4. Final Position	Flip 180°, edge 2 leading	85-100%	15%

### Rotation Timing Indicators

INDICATOR	MEASUREMENT	ACTION THRESHOLD
Leading edge wear	Depth gauge	>30mm from new
Weight loss	Scale comparison	>25% of new weight
Product coarseness	Sieve analysis	>15% coarser than target
Motor current increase	Ammeter	>10% above baseline

## Rotation Procedure

---

1. **Lock out/tag out** crusher and conveyor systems
2. **Document** bar positions and measurements before removal
3. **Remove** bars using proper lifting equipment
4. **Inspect** rotor mounting surfaces for damage
5. **Clean** mounting surfaces of all debris
6. **Rotate** bars according to schedule
7. **Verify** balance (weight difference <200g between opposing bars)
8. **Reinstall** with correct torque on fasteners
9. **Document** new positions and measurements

## Balance Requirements

ROTOR CONFIGURATION	MAXIMUM IMBALANCE	CONSEQUENCE IF EXCEEDED
2-bar rotor	200g between bars	Vibration, bearing wear
3-bar rotor	150g between bars	Uneven wear pattern
4-bar rotor	100g between opposing pairs	Reduced efficiency

## Cost-Benefit Analysis

---

Without Rotation:

- Bar cost: ₹40,000
- Life achieved: 35,000 tonnes
- Cost per tonne: ₹1.14

With 4-Position Rotation:

- Same bar cost: ₹40,000
- Life achieved: 60,000 tonnes
- Cost per tonne: ₹0.67

Savings: ₹0.47/tonne = 41% reduction

Annual savings (200 TPH × 3000 hrs): ₹2.8 lakhs

## Conclusion

---

Systematic blow bar rotation extracts 70-100% more life from the same initial investment. The 30-minute procedure per rotation returns hours of extended operation and significantly reduced wear costs. Track measurements consistently, rotate at appropriate intervals, and maintain balance—these simple practices transform blow bar economics from a necessary expense into a manageable, predictable operating cost.

---

**Topics:**

#Blow Bars

#HSI Crusher

#Maintenance

#Wear Parts