



**NESANS**

**MAINTENANCE TIPS**

# Vibrating Feeder Troubleshooting: Solve Common Feed Problems Quickly

Diagnose and fix vibrating feeder problems quickly. Uneven feed, low capacity, and vibration issues with practical solutions.

**Author:** Sivabalan  
Selvarajan

**Published:** March 2,  
2026

**Reading  
Time:** 6  
minutes

Vibrating feeders are the critical first stage in any crushing circuit, controlling material flow from hoppers and stockpiles to primary crushers. When feeders malfunction, the entire plant suffers—either from starvation causing low throughput, or surging that overloads downstream equipment. Understanding common vibrating feeder problems and their solutions enables operators to maintain consistent, efficient crushing operations.

# Understanding Vibrating Feeder Operation

## Feeder Types and Operating Principles

FEEDER TYPE	DRIVE MECHANISM	TYPICAL APPLICATION	CAPACITY RANGE
Grizzly feeder	Eccentric shaft or vibrating motors	Primary crusher feed with scalping	200-2000 TPH
Pan feeder	Eccentric shaft	General bulk material feeding	50-500 TPH
Electromagnetic feeder	Electromagnetic coil	Precise feed control, fine materials	1-200 TPH
Vibrating tube feeder	Vibrating motors	Enclosed feeding of fine materials	10-300 TPH

## Key Operating Parameters

Effective troubleshooting requires understanding normal operating parameters:

PARAMETER	TYPICAL RANGE	IMPACT OF DEVIATION
Vibrating frequency	850-1200 RPM	Affects material flow velocity
Stroke (amplitude)	4-12mm	Affects conveying rate and grizzly action
Deck angle	0° to -15°	Gravity assist vs material retention
Material bed depth	2-4 × largest particle	Uniform feeding vs surging
Motor current	60-80% of rated	Indicates loading and mechanical condition

## Problem 1: Inconsistent Feed Rate

### Symptoms

- Crusher amperage fluctuating significantly
- Variable product gradation

- Alternating high and low throughput periods
- Conveyor belt loading uneven

## Causes and Solutions

CAUSE	DIAGNOSTIC CHECK	SOLUTION
Hopper bridging	Visual inspection from above	Install bridge-breakers, adjust hopper angle
Material segregation in hopper	Observe feed pattern changes	Improve loading method, add flow aids
Variable material properties	Check moisture, size variation	Blend material, control moisture
Worn feeder deck	Inspect deck surface for holes/wear	Replace worn sections
Incorrect vibration settings	Measure stroke and frequency	Adjust to design parameters
Spring fatigue	Check spring height and condition	Replace springs in sets

## Hopper Design Factors

Many feeder problems originate in the hopper design:

Minimum hopper outlet dimensions:

Width:  $\geq 3 \times$  maximum lump size

Length:  $\geq 2.5 \times$  width

Hopper wall angles for mass flow:

Dry granular material: 60-65° from horizontal

Moist material: 65-70° from horizontal

Cohesive material: 70-75° from horizontal (consider live bottom)

## Problem 2: Low Feed Rate

---

### Symptoms

- Crusher running well below capacity

- Feeder appears to be running but material not moving
- Material building up on feeder deck

## Causes and Solutions

CAUSE	DIAGNOSTIC CHECK	SOLUTION
Insufficient stroke	Measure actual stroke	Adjust weights or replace worn eccentric
Low frequency (RPM)	Check motor speed and belt slip	Adjust drive, check electrical supply
Deck angle too flat	Measure installed angle	Adjust to recommended angle
Material buildup on deck	Visual inspection	Clean deck, improve material flow
Sticky material binding	Check material moisture	Install deck heaters, sprays, or liners
Overloaded deck	Observe material depth	Reduce hopper gate opening

## Stroke Adjustment Procedures

For eccentric shaft feeders:

1. Measure current stroke at multiple points
2. Adjust eccentric weights (if adjustable)
3. Verify uniform stroke across deck width
4. Recheck after 24-hour run-in period

For vibrating motor feeders:

1. Check motor weight adjustment setting
2. Verify both motors rotating in correct direction
3. Adjust centrifugal weights equally on both motors
4. Confirm motor synchronization

## Problem 3: Excessive Vibration or Noise

### Symptoms

- Abnormal noise during operation
- Visible excessive movement of feeder frame
- Foundation bolt loosening
- Nearby equipment affected by transmitted vibration

### Causes and Solutions

CAUSE	DIAGNOSTIC CHECK	SOLUTION
Broken spring	Visual inspection, height measurement	Replace springs in matched sets
Loose structural bolts	Torque check all connections	Re-torque to specification
Unbalanced rotating parts	Vibration analysis	Check eccentric weights, replace worn parts
Bearing failure	Temperature check, noise analysis	Replace bearings
Motor timing incorrect	Check motor counter-rotation	Reverse one motor connection
Foundation settlement	Level check, gap inspection	Re-level and re-grout foundation

### Spring System Maintenance

Springs are critical to proper feeder operation:

SPRING TYPE	INSPECTION INTERVAL	REPLACEMENT CRITERIA
Coil springs	Weekly visual, monthly measurement	>5% height loss or visible damage
Rubber springs	Monthly visual	Cracking, chunking, permanent set
Air springs	Daily pressure check	Pressure loss, visible damage

## Problem 4: Grizzly Bars Plugging or Blinding

### Symptoms

- Fines not passing through grizzly
- Scalping efficiency reduced
- Crusher receiving excessive fines
- Material building up between bars

### Causes and Solutions

CAUSE	DIAGNOSTIC CHECK	SOLUTION
Bar spacing too narrow	Measure gap vs material fines size	Increase spacing or use different bar profile
Sticky material	Check moisture content	Install bar heaters, vibration intensifiers
Insufficient vibration	Measure stroke amplitude	Increase stroke or frequency
Flat-topped bars	Inspect bar profile	Replace with tapered or stepped bars
Material compaction	Observe flow pattern	Reduce bed depth, increase deck angle

### Grizzly Bar Selection Guide

BAR TYPE	BEST APPLICATION	ADVANTAGES
Flat bar	Dry, free-flowing material	Simple, economical
Tapered bar	Sticky or moist material	Wedge action prevents plugging
Stepped bar	Very sticky material	Multiple release points
Finger screen deck	Wet screening applications	Flexible, self-cleaning action

## Problem 5: Premature Wear

### Symptoms

- Frequent liner replacement
- Holes developing in deck
- Grizzly bars wearing rapidly
- Increasing maintenance costs

### Causes and Solutions

CAUSE	DIAGNOSTIC CHECK	SOLUTION
Abrasive material	Material hardness testing	Upgrade to AR plate or ceramic liners
High impact loading	Observe loading pattern	Install rock box, reduce drop height
Incorrect liner material	Compare wear rate to alternatives	Select appropriate wear material
Excessive stroke	Measure and compare to design	Reduce to recommended amplitude
Uneven material distribution	Observe wear pattern	Improve feed point distribution

### Liner Material Selection

MATERIAL	HARDNESS	BEST APPLICATION	RELATIVE LIFE
Mild steel	150 HB	Low abrasion, minimal impact	1.0x
Hardox 400	400 HB	General crushing duty	2.5-3.0x
Hardox 500	500 HB	High abrasion, moderate impact	3.5-4.5x
Ceramic tile	1400 HV	Sliding abrasion, low impact	6-10x
Chromium carbide overlay	60 HRC	Severe sliding abrasion	5-8x

## Problem 6: Drive System Issues

---

### Eccentric Shaft Drive Problems

SYMPTOM	PROBABLE CAUSE	SOLUTION
High motor current	Overloading, bearing friction	Check load, inspect bearings
Belt slipping	Incorrect tension, worn belts	Adjust tension, replace belts
Bearing overheating	Lubrication failure, overload	Check grease, reduce load
Oil leaks	Seal failure	Replace seals, check shaft condition
Unusual noise	Bearing damage, loose parts	Inspect thoroughly, replace worn parts

### Vibrating Motor Drive Problems

SYMPTOM	PROBABLE CAUSE	SOLUTION
Motors running hot	Overload, poor ventilation	Check amperage, clean motor fins
Uneven vibration	Motor weight adjustment different	Match weight settings on both motors
Motors not synchronized	One motor running backwards	Correct motor wiring
Rapid bearing failure	Operating outside rated parameters	Check stroke, frequency within ratings
Cable damage	Insufficient cable loop, abrasion	Provide adequate service loop, protect cables

## Preventive Maintenance Schedule

---

### Daily Checks

- Visual inspection for material buildup
- Listen for abnormal sounds

- Check motor temperature (by touch or IR)
- Verify feed rate consistency
- Inspect for obvious damage or wear

## Weekly Maintenance

- Check all structural bolt tightness
- Inspect spring condition
- Measure and record motor amperage
- Grease bearings per schedule
- Clean debris from around feeder

## Monthly Maintenance

- Measure stroke amplitude
- Check spring free height
- Inspect drive belts (if equipped)
- Check liner and grizzly bar wear
- Verify electrical connections

## Annual Maintenance

- Complete bearing inspection or replacement
- Spring replacement if required
- Drive component inspection
- Frame structural inspection
- Foundation bolt retorquing

## Troubleshooting Decision Tree

---

### Start: Feeder not conveying material at expected rate

1. Is material reaching the feeder deck?
  - No → Check hopper for bridging, low level, gate position

- Yes → Continue to step 2

## 2. Is the feeder vibrating normally?

- No vibration → Check power supply, motor, controls
- Low vibration → Check stroke, springs, drive
- Normal vibration → Continue to step 3

## 3. Is material moving on deck but slowly?

- Yes → Check deck angle, material buildup, moisture
- Material not moving → Check for mechanical binding

## 4. Is grizzly section working properly?

- Plugged → Check spacing, stroke, material moisture
- Clear but fines not passing → Increase vibration

Systematic troubleshooting based on understanding feeder operation principles enables rapid diagnosis and resolution of most vibrating feeder problems. Regular preventive maintenance prevents most issues from developing into production-limiting failures.

---

**Topics:**

#Feed System

#Troubleshooting

#Vibratory Feeder